



MOTOR FRAMES	C	HA	HB	HE	HF	HF ₁	MO
445 TS	40.5	30.0	96.0	14.19	92.0	46.0	11.8
447 TS	44.0	30.0	96.0	14.19	92.0	46.0	11.8
449 TS	44.6	30.0	96.0	14.19	92.0	46.0	11.8
503 US	36.0	30.0	96.0	14.19	92.0	46.0	14.0
504 US	41.8	30.0	96.0	14.19	92.0	46.0	14.0

NOTES

1. All Dimensions are in inches.
2. Suction and discharge connections are 125 ANSI B16.1, Standard Flanges.
3. Baseplate setting (before piping) grouting procedures and final alignment must be in accordance with ITT A-C Pump recommended procedures outlined in the Instruction Manual associated with this pump type.
4. Motor dimensions are approximate for a given NEMA frame. Consult factory if space is limited.
5. Both suction and discharge pipes must be supported independently near the pump to reduce strain on the pump casing. Also expansion joints if used must not exert force on casing.
6. "H" High Pressure Pumps over 250 psi working pressure will have 250 ANSI B16.1 suction and discharge flanges.

NOT FOR CONSTRUCTION, INSTALLATION OR APPLICATION PURPOSES UNLESS CERTIFIED.							
CERTIFIED FOR:						APPROVAL <input type="checkbox"/> UL <input type="checkbox"/> FM	
CUSTOMER ORDER NO:				IDENTIFICATION NO:			
PUMP DATA	SIZE & TYPE	MODEL	CURVE NO.	GPM	HEAD (PSI)	ROTATION	FLANGES
MOTOR DATA	HP	RPM	VOLTS	PHASE	HERTZ	FRAME SIZE	ENCLOSURE
SHOP ORDER:				CERTIFIED BY:		DATE	